

This specification describes articles of the material group

Sugar cane fibres with PBAT lamination

Material description:

The sugar cane is rolled and pressed in order to obtain the syrup. The fibres are ground into a fine paste with the addition of water and natural binders and then processed and pressed into moulds and subsequently with PBAT foil sealed. PBAT - polybutyrate is a biodegradable copolymer.

	<p>Tray square Article number 12857</p>
	<p>Tray rectangular Article numbers 12858, 12859, 12860, 13049</p>
	<p>Tray rectangular, 2 -compartments Article number 12861</p>
	<p>Menu tray, 1-compartment Article numbers 12895</p>
	<p>Menu tray, 2-compartment Article number 12896</p>
	<p>Menu tray, 3-compartment Article number 12897</p>

These informations are based on our current knowledge and understanding. Specifications may be adjusted at any time, without prior notice.

Material / Composition

Material: sugar cane with PBAT lamination

Packaging / Storage

Storage temperature room temperature, protect against sun exposure
Storage humidity dry

Compostability:

Compostability certification
Products tested according to EN13432:2000-12
Certificate no 7P0456

Customs duty number: 4823.7000

Pacovis AG

Pacovis AG
Grabenmattenstrasse 19
CH-5608 Stetten
phone +41 56 485 93 93 /fax. +41 56 485 93 00
www.pacovis.ch

These informations are based on our current knowledge and understanding. Specifications may be adjusted at any time, without prior notice.



Declaration of conformity

These articles meet the following regulations and are suitable for direct contact with food :

EU-Regulation 2004/1935/EC on materials and articles intended to come into contact with food with possible amendments.

EU- Regulation 2023/2006 on good manufacturing practice for materials and articles intended to come into contact with food with possible amendments.

EU-Regulation 10/2011/EC relating to plastic materials and articles intended to come into contact with foodstuffs with possible amendments.

EU-Directive 94/62/EC on packaging and packaging waste (heavy metal content)

Purpose of use

- These articles are suitable for single usage as packaging of wet, fatty and milk base foods - short term contact
- Suitable for microwave up to 400 watt, max. 10 minutes
- Suitable for oven up to 200 °C max. 30 minutes
- Freezability: to – 25° C

Overall migration limit

Tested under the following conditions

- 2 hours at 70°C in water
- 2 hours at 60°C in 50% ethanol
- 2 hours at 70°C in olive oil
- 30 minutes at 200°C in tenax
- **10 days at 20°C in 3% acetic acid, 50% ethanol, olive oil

The overall migration limits have not exceed the value of 60mg/dm² or 10mg/dm².

**The overall migration limit with the simulants 3% acetic acid, 50% ethanol does not exceed the limit of 60mg/kg or 10mg/dm². The overall migration limit with olive oil does exceed the limit.

Only the application of a reduction factor of ≥ 2 complies with the requirements of the EU-Regulation 10/2011/EC.

Specific migration

The following substances have specific migration restrictions listed in Regulation (EU) no 10/2011 :

Substance	CAS-No	Limit mg/kg	Value mg/kg
Terephthalic acid	0000100-21-0	7.5	<7.5

The calculations are based on the assumption that 1 kg of food comes into contact with the packaging material 6dm².

Heavy metals: lead, cadmium, mercury and chromium is below the legal limit.

The limit values of 100 mg / kg is not exceeded.

These informations are based on our current knowledge and understanding. Specifications may be adjusted at any time, without prior notice.